United States Patent	[19]				
Maass et al.					

[11]	Patent Number:	1.5
[45]	Date of Patent:	No

4,553,545 Nov. 19, 1985

[54]	DEVICE FOR APPLICATION IN BLOOD VESSELS OR OTHER DIFFICULTLY ACCESSIBLE LOCATIONS AND ITS USE			
[75]		Wall	k Maass, Zürich; Hans I. stén, Denens, both of zerland	
[73]			invent S.A., Lausanne, zerland	
[21]	Appl. No.:		498,189	
[22]	PCT Filed:		Sep. 15, 1982	
[86]	PCT No.:		PCT/SE82/00283	
	§ 371 Date:		May 5, 1983	
	§ 102(e) Dat	te:	May 5, 1983	
[87]	PCT Pub. N	lo.:	WO83/00997	
	PCT Pub. D	ate:	Mar. 31, 1983	
[30]	Foreign	Appl	ication Priority Data	
Sep Apr	. 16, 1981 [SE . 30, 1982 [SE] S] S	weden 8105510 weden 8202740	
			A61M 29/00; C21B 15/00	
[58]	Field of Sear	ch	128/341, 345, 334 R;	

[56]	References Cited		
	U.S. PATENT DOCUMENTS		


		DibeliusAlfidi et al	
3,993,078	11/1976	Bergentz et al	128/334
4,130,904	12/1978	Whalen	128/334 R X
4,503,569	3/1985	Dotter	128/334 R X
4,512,338	4/1985	Balko et al	128/341 X

Primary Examiner—William H. Grieb Attorney, Agent, or Firm—Burns, Doane, Swecker & Mathis

[57] ABSTRACT

Device comprising a helically shaped spiral spring and means for bringing the spring to expand from a first state of a certain diameter to a second state of larger diameter and vice versa, characterized thereby that said means are arranged to rotate the ends of the spring relative to each other with maintained length of the spring so that the transition from said first state to said second state takes place by reducing the number of spring turns within said length and the corresponding increase of the pitch of the spring, or to supply to a given length of the spring further spring material at at least one end of the said length of the spring so that the transition from said first state to said second state takes place independent of pitch and number of spring turns within the said length; and a method for transluminal implantation of an intravascular prosthesis using the said device.

19 Claims, 29 Drawing Figures



604/104; 267/167, 170